CS162
Operating Systems and Systems Programming
Lecture 16

Memory 4: Demand Paging Policies

March 15th, 2022

Prof. Anthony Joseph and John Kubiatowicz
http://cs162.eecs.Berkeley.edu

Recall 61C: Average Memory Access Time

- Used to compute access time probabilistically:

$AMAT = Hit\ Rate_{L1} \times Hit\ Time_{L1} + Miss\ Rate_{L1} \times Miss\ Time_{L1}$

$Hit\ Rate_{L1} + Miss\ Rate_{L1} = 1$
$Hit\ Time_{L1}$ = Time to get value from L1 cache.
$Miss\ Time_{L1} = Hit\ Time_{L1} + Miss\ Penalty_{L1}$
$Miss\ Penalty_{L1}$ = AVG Time to get value from lower level (DRAM)

So, $AMAT = Hit\ Time_{L1} + Miss\ Rate_{L1} \times Miss\ Penalty_{L1}$



- What about more levels of hierarchy?

$AMAT = Hit\ Time_{L1} + Miss\ Rate_{L1} \times Miss\ Penalty_{L1}$

$Miss\ Penalty_{L1}$ = AVG time to get value from lower level (L2)
$= Hit\ Time_{L2} + Miss\ Rate_{L2} \times Miss\ Penalty_{L2}$

$Miss\ Penalty_{L2}$ = Average Time to fetch from below L2 (DRAM)

$AMAT = Hit\ Time_{L1} +$
$Miss\ Rate_{L1} \times (Hit\ Time_{L2} + Miss\ Rate_{L2} \times Miss\ Penalty_{L2})$



- And so on … (can do this recursively for more levels!)

Recall: Caching Applied to Address Translation



- Question is one of page locality: does it exist?
  - Instruction accesses spend a lot of time on the same page (accesses sequential)
  - Stack accesses have definite locality of reference
  - Data accesses have less page locality, but still some…
- Can we have a TLB hierarchy?
  - Sure: multiple levels at different sizes/speeds

Management & Access to the Memory Hierarchy



Page Fault ⇒ Demand Paging



Demand Paging as Caching, …

- What "block size"? - 1 page (e.g, 4 KB)
- What "organization" ie. direct-mapped, set-assoc., fully-associative?
  - Fully associative since arbitrary virtual → physical mapping
- How do we locate a page?
  - First check TLB, then page-table traversal
- What is page replacement policy? (i.e. LRU, Random…)
  - This requires more explanation… (kinda LRU)
- What happens on a miss?
  - Go to lower level to fill miss (i.e. disk)
- What happens on a write? (write-through, write back)
  - Definitely write-back – need dirty bit!

Illusion of Infinite Memory



- Disk is larger than physical memory ⇒
  - In-use virtual memory can be bigger than physical memory
  - Combined memory of running processes much larger than physical memory
    - » More programs fit into memory, allowing more concurrency
- Principle: Transparent Level of Indirection (page table)
  - Supports flexible placement of physical data
    - » Data could be on disk or somewhere across network
  - Variable location of data transparent to user program
    - » Performance issue, not correctness issue

Review: What is in a PTE?

- What is in a Page Table Entry (or PTE)?
  - Pointer to next-level page table or to actual page
  - Permission bits: valid, read-only, read-write, write-only
- Example: Intel x86 architecture PTE:
  - 2-level page tabler (10, 10, 12-bit offset)
  - Intermediate page tables called "Directories"



P: Present (same as "valid" bit in other architectures)
W: Writeable
U: User accessible
PWT: Page write transparent: external cache write-through
PCD: Page cache disabled (page cannot be cached)
A: Accessed: page has been accessed recently
D: Dirty (PTE only): page has been modified recently
PS: Page Size: PS=1⇒4MB page (directory only).
Bottom 22 bits of virtual address serve as offset

Demand Paging Mechanisms

- PTE makes demand paging implementatable
  - Valid ⇒ Page in memory, PTE points at physical page
  - Not Valid ⇒ Page not in memory; use info in PTE to find it on disk when necessary
- Suppose user references page with invalid PTE?
  - Memory Management Unit (MMU) traps to OS
    - » Resulting trap is a "Page Fault"
  - What does OS do on a Page Fault?:
    - » Choose an old page to replace
    - » If old page modified ("D=1"), write contents back to disk
    - » Change its PTE and any cached TLB to be invalid
    - » Load new page into memory from disk
    - » Update page table entry, invalidate TLB for new entry
    - » Continue thread from original faulting location
  - TLB for new page will be loaded when thread continued!
  - While pulling pages off disk for one process, OS runs another process from ready queue
    - » Suspended process sits on wait queue

Origins of Paging



Very Different Situation Today



A Picture on one machine

```
Processes: 407 total, 2 running, 405 sleeping, 2135 threads                                                 22:10:39
Load Avg: 1.26, 1.26, 0.98  CPU usage: 1.35% user, 1.59% sys, 97.5% idle
SharedLibs: 292M resident, 54M data, 43M linkedit.
MemRegions: 155071 total, 4489M resident, 124M private, 1891M shared.
PhysMem: 13G used (3518M wired), 2718M unused.
VM: 1819G vsize, 1372M framework vsize, 68020510(0) swapins, 71200340(0) swapouts.
Networks: packets: 40629441/21G in, 21395374/7747M out.
Disks: 17026780/555G read, 15757470/638G written.

PID    COMMAND      %CPU  TIME     #TH   #WQ  #PORTS MEM    PURG   CMPRS  PGRP  PPID  STATE
90498  bash         0.0   00:00.41 1     0    21     1080K  0B     564K   90498 90497 sleeping
90497  login        0.0   00:00.10 2     1    31     1236K  0B     1220K  90497 90496 sleeping
90496  Terminal     0.5   01:43.28 6     1    378-   103M-  16M    13M    90496 1     sleeping
89197  siriknowledg 0.0   00:00.83 2     2    45     2664K  0B     1528K  89197 1     sleeping
89193  com.apple.DF 0.0   00:17.34 2     1    68     2688K  0B     1700K  89193 1     sleeping
82655  LookupViewSe 0.0   00:10.75 3     1    169    13M    0B     8064K  82655 1     sleeping
82453  PAH_Extensio 0.0   00:25.89 3     1    235    15M    0B     7996K  82453 1     sleeping
75819  tzlinkd      0.0   00:00.01 2     2    14     452K   0B     444K   75819 1     sleeping
75787  MTLCompilerS 0.0   00:00.10 2     2    24     9032K  0B     9020K  75787 1     sleeping
75776  secd         0.0   00:00.78 2     2    36     3208K  0B     2328K  75776 1     sleeping
75098  DiskUnmountW 0.0   00:00.48 2     2    34     1428K  0B     728K   75098 1     sleeping
75093  MTLCompilerS 0.0   00:00.06 2     2    21     5924K  0B     5912K  75093 1     sleeping
74938  ssh-agent    0.0   00:00.00 1     0    21     908K   0B     892K   74938 1     sleeping
74063  Google Chrom 0.0   10:48.49 15    1    678    192M   0B     51M    54320 54320 sleeping
```

- Memory stays about 75% used, 25% for dynamics
- A lot of it is shared 1.9 GB

Many Uses of Virtual Memory and "Demand Paging" …

- Extend the stack
  - Allocate a page and zero it
- Extend the heap (sbrk of old, today mmap)
- Process Fork
  - Create a copy of the page table
  - Entries refer to parent pages – NO-WRITE
  - Shared read-only pages remain shared
  - Copy page on write
- Exec
  - Only bring in parts of the binary in active use
  - Do this on demand
- MMAP to explicitly share region (or to access a file as RAM)

Classic: Loading an executable into memory



- .exe
  - lives on disk in the file system
  - contains contents of code & data segments, relocation entries and symbols
  - OS loads it into memory, initializes registers (and initial stack pointer)
  - program sets up stack and heap upon initialization: `crt0` (C runtime init)

Create Virtual Address Space of the Process



- Utilized pages in the VAS are backed by a page block on disk
  - Called the backing store or swap file
  - Typically in an optimized block store, but can think of it like a file

Create Virtual Address Space of the Process



- User Page table maps entire VAS
- All the utilized regions are backed on disk
  - swapped into and out of memory as needed
- For *every* process

Create Virtual Address Space of the Process



- User Page table maps entire VAS
  - Resident pages to the frame in memory they occupy
  - The portion of it that the HW needs to access must be resident in memory

Provide Backing Store for VAS



- User Page table maps entire VAS
- Resident pages mapped to memory frames
- For all other pages, OS must record where to find them on disk

What Data Structure Maps Non-Resident Pages to Disk?

- `FindBlock(PID, page#)` → `disk_block`
  - Some OSs utilize spare space in PTE for paged blocks
  - Like the PT, but purely software
- Where to store it?
  - In memory – can be compact representation if swap storage is contiguous on disk
  - Could use hash table (like Inverted PT)
- Usually want backing store for resident pages too
- May map code segment directly to on-disk image
  - Saves a copy of code to swap file
- May share code segment with multiple instances of the program

Provide Backing Store for VAS



On page Fault …



On page Fault … find & start load



On page Fault … schedule other P or T



On page Fault … update PTE



Eventually reschedule faulting thread



Summary: Steps in Handling a Page Fault



Some questions we need to answer!

- During a page fault, where does the OS get a free frame?
  - Keeps a free list
  - Unix runs a "reaper" if memory gets too full
    - » Schedule dirty pages to be written back on disk
    - » Zero (clean) pages which haven't been accessed in a while
  - As a last resort, evict a dirty page first
- How can we organize these mechanisms?
  - Work on the replacement policy
- How many page frames/process?
  - Like thread scheduling, need to "schedule" memory resources:
    - » Utilization? fairness? priority?
  - Allocation of disk paging bandwidth

Working Set Model

- As a program executes it transitions through a sequence of "working sets" consisting of varying sized subsets of the address space



Cache Behavior under WS model



- Amortized by fraction of time the Working Set is active
- Transitions from one WS to the next
- Capacity, Conflict, Compulsory misses
- Applicable to memory caches and pages. Others ?

Another model of Locality: Zipf



- Likelihood of accessing item of rank r is α $1/r^a$
- Although rare to access items below the top few, there are so many that it yields a "heavy tailed" distribution
- Substantial value from even a tiny cache
- Substantial misses from even a very large cache

Demand Paging Cost Model

- Since Demand Paging like caching, can compute average access time! ("Effective Access Time")
  - EAT = Hit Rate x Hit Time + Miss Rate x Miss Time
  - EAT = Hit Time + Miss Rate x Miss Penalty
- Example:
  - Memory access time = 200 nanoseconds
  - Average page-fault service time = 8 milliseconds
  - Suppose p = Probability of miss, 1-p = Probably of hit
  - Then, we can compute EAT as follows:

    EAT = 200ns + p x 8 ms
    = 200ns + p x 8,000,000ns
- If one access out of 1,000 causes a page fault, then EAT = 8.2 μs:
  - This is a slowdown by a factor of 40!
- What if want slowdown by less than 10%?
  - EAT < 200ns x 1.1 ⇒ p < 2.5 x 10^{-6}
  - This is about 1 page fault in 400,000!

What Factors Lead to Misses in Page Cache?

- Compulsory Misses:
  - Pages that have never been paged into memory before
  - How might we remove these misses?
    - » Prefetching: loading them into memory before needed
    - » Need to predict future somehow! More later
- Capacity Misses:
  - Not enough memory. Must somehow increase available memory size.
  - Can we do this?
    - » One option: Increase amount of DRAM (not quick fix!)
    - » Another option: If multiple processes in memory: adjust percentage of memory allocated to each one!
- Conflict Misses:
  - Technically, conflict misses don't exist in virtual memory, since it is a "fully-associative" cache
- Policy Misses:
  - Caused when pages were in memory, but kicked out prematurely because of the replacement policy
  - How to fix? Better replacement policy

Administrivia

- Midterm 2: Coming up on Thursday 3/17 7-9pm
  - Topics: up until Lecture 16 (today): Scheduling, Deadlock, Address Translation, Virtual Memory, Caching, TLBs, Demand Paging
- Review Session was yesterday
  - Slides and recording are available on the course website

Page Replacement Policies

- Why do we care about Replacement Policy?
  - Replacement is an issue with any cache
  - Particularly important with pages
    - » The cost of being wrong is high: must go to disk
    - » Must keep important pages in memory, not toss them out
- FIFO (First In, First Out)
  - Throw out oldest page. Be fair – let every page live in memory for same amount of time.
  - Bad – throws out heavily used pages instead of infrequently used
- RANDOM:
  - Pick random page for every replacement
  - Typical solution for TLB's. Simple hardware
  - Pretty unpredictable – makes it hard to make real-time guarantees
- MIN (Minimum):
  - Replace page that won't be used for the longest time
  - Great (provably optimal), but can't really know future…
  - But past is a good predictor of the future …

Replacement Policies (Con't)

- LRU (Least Recently Used):
  - Replace page that hasn't been used for the longest time
  - Programs have locality, so if something not used for a while, unlikely to be used in the near future.
  - Seems like LRU should be a good approximation to MIN.
- How to implement LRU? Use a list:



  - On each use, remove page from list and place at head
  - LRU page is at tail
- Problems with this scheme for paging?
  - Need to know immediately when page used so that can change position in list…
  - Many instructions for each hardware access
- In practice, people approximate LRU (more later)

Example: FIFO (strawman)

- Suppose we have 3 page frames, 4 virtual pages, and following reference stream:
  - A B C A B D A D B C B
- Consider FIFO Page replacement:

Ref: / Page:	A	B	C	A	B	D	A	D	B	C	B
1	A					D				C	
2		B					A				
3			C						B		

- FIFO: 7 faults
- When referencing D, replacing A is bad choice, since need A again right away

Example: MIN / LRU

- Suppose we have the same reference stream:
  - A B C A B D A D B C B
- Consider MIN Page replacement:

Ref: Page:	A	B	C	A	B	D	A	D	B	C	B
1	A									C	
2		B									
3			C			D					

- MIN: 5 faults
  - Where will D be brought in? Look for page not referenced farthest in future
- What will LRU do?
  - Same decisions as MIN here, but won't always be true!

Is LRU guaranteed to perform well?

- Consider the following: A B C D A B C D A B C D
- LRU Performs as follows (same as FIFO here):

Ref: Page:	A	B	C	D	A	B	C	D	A	B	C	D
1	A			D			C			B		
2		B			A			D			C	
3			C			B			A			D

  - Every reference is a page fault!
- Fairly contrived example of working set of N+1 on N frames

When will LRU perform badly?

- Consider the following: A B C D A B C D A B C D
- LRU Performs as follows (same as FIFO here):

Ref: Page:	A	B	C	D	A	B	C	D	A	B	C	D
1	A			D			C			B		
2		B			A			D			C	
3			C			B			A			D

  - Every reference is a page fault!
- MIN Does much better:

Ref: Page:	A	B	C	D	A	B	C	D	A	B	C	D
1	A									B		
2		B					C					
3			C	D								

Graph of Page Faults Versus The Number of Frames



- One desirable property: When you add memory the miss rate drops (stack property)
  - Does this always happen?
  - Seems like it should, right?
- No: Bélády's anomaly
  - Certain replacement algorithms (FIFO) don't have this obvious property!

Adding Memory Doesn't Always Help Fault Rate

- Does adding memory reduce number of page faults?
  - Yes for LRU and MIN
  - Not necessarily for FIFO! (Called Bélády's anomaly)

Ref:	A	B	C	D	A	B	E	A	B	C	D	E
Page 1	A			D			E					
2		B			A					C		
3			C			B					D	

Ref:	A	B	C	D	A	B	E	A	B	C	D	E
Page 1	A						E				D	
2		B						A				E
3			C						B			
4				D						C		

- After adding memory:
  - With FIFO, contents can be completely different
  - In contrast, with LRU or MIN, contents of memory with X pages are a subset of contents with X+1 Page

Approximating LRU: Clock Algorithm



- Clock Algorithm: Arrange physical pages in circle with single clock hand
  - Approximate LRU (*approximation to approximation to MIN*)
  - Replace an old page, not the oldest page
- Details:
  - Hardware "use" bit per physical page (called "accessed" in Intel architecture):
    - » Hardware sets use bit on each reference
    - » If use bit isn't set, means not referenced in a long time
    - » Some hardware sets use bit in the TLB; must be copied back to PTE when TLB entry gets replaced
  - On page fault:
    - » Advance clock hand (not real time)
    - » Check use bit: 1→ used recently; clear and leave alone
      0→ selected candidate for replacement

Clock Algorithm: More details



- Will always find a page or loop forever?
  - Even if all use bits set, will eventually loop all the way around ⇒ FIFO
- What if hand moving slowly?
  - Good sign or bad sign?
    - » Not many page faults
    - » or find page quickly
- What if hand is moving quickly?
  - Lots of page faults and/or lots of reference bits set
- One way to view clock algorithm:
  - Crude partitioning of pages into two groups: young and old
  - Why not partition into more than 2 groups?

Nth Chance version of Clock Algorithm

- Nth chance algorithm: Give page N chances
  - OS keeps counter per page: # sweeps
  - On page fault, OS checks use bit:
    - » 1 → clear use and also clear counter (used in last sweep)
    - » 0 → increment counter; if count=N, replace page
  - Means that clock hand has to sweep by N times without page being used before page is replaced
- How do we pick N?
  - Why pick large N? Better approximation to LRU
    - » If N ~ 1K, really good approximation
  - Why pick small N? More efficient
    - » Otherwise might have to look a long way to find free page
- What about "modified" (or "dirty") pages?
  - Takes extra overhead to replace a dirty page, so give dirty pages an extra chance before replacing?
  - Common approach:
    - » Clean pages, use N=1
    - » Dirty pages, use N=2 (and write back to disk when N=1)

Recall: Meaning of PTE bits

- Which bits of a PTE entry are useful to us for the Clock Algorithm? Remember Intel PTE:



  - The "Present" bit (called "Valid" elsewhere):
    - » P==0: Page is invalid and a reference will cause page fault
    - » P==1: Page frame number is valid and MMU is allowed to proceed with translation
  - The "Writable" bit (could have opposite sense and be called "Read-only"):
    - » W==0: Page is read-only and cannot be written.
    - » W==1: Page can be written
  - The "Accessed" bit (called "Use" elsewhere):
    - » A==0: Page has not been accessed (or used) since last time software set A→0
    - » A==1: Page has been accessed (or used) since last time software set A→0
  - The "Dirty" bit (called "Modified" elsewhere):
    - » D==0: Page has not been modified (written) since PTE was loaded
    - » D==1: Page has changed since PTE was loaded

Clock Algorithms Variations

- Do we really need hardware-supported "modified" bit?
  - No. Can emulate it using read-only bit
    - » Need software DB of which pages are allowed to be written (needed this anyway)
    - » We will tell MMU that pages have more restricted permissions than the actually do to force page faults (and allow us notice when page is written)
  - Algorithm (Clock-Emulated-M):
    - » Initially, mark all pages as read-only (W→0), even writable data pages. Further, clear all software versions of the "modified" bit → 0 (page not dirty)
    - » Writes will cause a page fault. Assuming write is allowed, OS sets software "modified" bit → 1, and marks page as writable (W→1).
    - » Whenever page written back to disk, clear "modified" bit → 0, mark read-only

Clock Algorithms Variations (continued)

- Do we really need a hardware-supported "use" bit?
  - No. Can emulate it similar to above (e.g. for read operation)
    - » Kernel keeps a "use" bit and "modified" bit for each page
  - Algorithm (Clock-Emulated-Use-and-M):
    - » Mark all pages as invalid, even if in memory. Clear emulated "use" bits → 0 and "modified" bits → 0 for all pages (not used, not dirty)
    - » Read or write to invalid page traps to OS to tell use page has been used
    - » OS sets "use" bit → 1 in software to indicate that page has been "used". Further:
      1) If read, mark page as read-only, W→0 (will catch future writes)
      2) If write (and write allowed), set "modified" bit → 1, mark page as writable (W→1)
    - » When clock hand passes, reset emulated "use" bit → 0 and mark page as invalid again
    - » Note that "modified" bit left alone until page written back to disk
- Remember, however, clock is just an approximation of LRU!
  - Can we do a better approximation, given that we have to take page faults on some reads and writes to collect use information?
  - Need to identify an old page, not oldest page!
  - Answer: second chance list

Second-Chance List Algorithm (VAX/VMS)



- Split memory in two: Active list (RW), SC list (Invalid)
- Access pages in Active list at full speed
- Otherwise, Page Fault
  - Always move overflow page from end of Active list to front of Second-chance list (SC) and mark invalid
  - Desired Page On SC List: move to front of Active list, mark RW
  - Not on SC list: page in to front of Active list, mark RW; page out LRU victim at end of SC list

Second-Chance List Algorithm (continued)

- How many pages for second chance list?
  - If 0 ⇒ FIFO
  - If all ⇒ LRU, but page fault on every page reference
- Pick intermediate value. Result is:
  - Pro: Few disk accesses (page only goes to disk if unused for a long time)
  - Con: Increased overhead trapping to OS (software / hardware tradeoff)
- With page translation, we can adapt to any kind of access the program makes
  - Later, we will show how to use page translation / protection to share memory between threads on widely separated machines
- History: The VAX architecture did not include a "use" bit.
  Why did that omission happen???
  - Strecker (architect) asked OS people, they said they didn't need it, so didn't implement it
  - He later got blamed, but VAX did OK anyway

Summary

- Replacement policies
  - FIFO: Place pages on queue, replace page at end
  - MIN: Replace page that will be used farthest in future
  - LRU: Replace page used farthest in past
- Clock Algorithm: Approximation to LRU
  - Arrange all pages in circular list
  - Sweep through them, marking as not "in use"
  - If page not "in use" for one pass, than can replace
- N^{th}-chance clock algorithm: Another approximate LRU
  - Give pages multiple passes of clock hand before replacing
- Second-Chance List algorithm: Yet another approximate LRU
  - Divide pages into two groups, one of which is truly LRU and managed on page faults.
- Working Set:
  - Set of pages touched by a process recently
- Thrashing: a process is busy swapping pages in and out
  - Process will thrash if working set doesn't fit in memory
  - Need to swap out a process