

EECS16A Imaging 2



Agenda

- Quick overview + review
- Images as matrices and vectors
- Pixel-by-pixel scanning
- Reconstructing scans as images
- Lab-specific simulation directions



-



Today's Lab: Single Pixel Scanning

- Circuit from last week measures **light** intensity
- Simulated projector illuminates image in a controlled way
- Python programming to reconstruct image



Why?

- Imaging 1:
 - Finding a link between physical quantities and voltage is powerful
 - If you can digitize it, you can do anything (IOT devices, internet, code, processing)
- Imaging 2:
 - What measurements are good measurements?
 - Remember Kody and Nara from Dis0C?



Kody and Nara

2. Finding The Bright Cave

Nara the one-handed druid and Kody the one-handed ranger find themselves in dire straits. Before them is a cliff with four cave entrances arranged in a square: two upper caves and two lower caves. Each entrance emits a certain amount of light, and the two wish to find exactly the amount of light coming from each cave. Here's the catch: after contracting a particularly potent strain of ghoulish fever, our intrepid heroes are only able to see the total intensity of light before them (so their eyes operate like a single-pixel camera). Kody and Nara are capable adventurers, but they don't know any linear algebra – and they need your help.

Kody proposes an imaging strategy where he uses his hand to completely block the light from two caves at a time. He is able to take measurements using the following four masks (black means the light is blocked from that cave):




Figure 1: Four image masks.



- Let $\vec{x}$ be the four-element vector that represents the magnitude of light emanating from the four cave entrances. Write a matrix $\mathbf{K}$ that performs the masking process in Figure 1 on the vector $\vec{x}$, such that $\mathbf{K}\vec{x}$ is the result of the four measurements.
- Does Kody's set of masks give us a unique solution for all four caves' light intensities? Why or why not?
- Nara, in her infinite wisdom, places her one hand diagonally across the entrances, covering two of the cave entrances. However, her hand is not wide enough, letting in 50% of the light from the caves covered and 100% of the light from the caves not covered. The following diagram shows the percentage of light let through from each cave:

- Linear dependence
 - When can you recover your image?
 - Does it matter what mask matrix you pick?
 - Does it matter how you cover the pixels?
- Invertibility
 - When can you solve $Ax = b$?
 - How does this relate to our system?
 - How does this affect the way we pick our masking matrix?

Real-life Setup



Power strip to
power your
projector




PROJECTOR

OBJECT BEING IMAGED

LAUNCHPAD

SENSOR CIRCUIT




Real-life Setup (cont.)

1. Draw a “simple” image
2. Project masks (rows of H) onto it in a dark environment
3. Measure ambient light sensor reading $\mathbf{s}$
4. Multiply by H inverse to find $\mathbf{i}$ ($= H^{-1} \cdot \mathbf{s}$)



Sample Real-Life Setup Images



This Lab: Software Simulator Setup

1. Upload (“simple”) image of an object (or use default)
2. Shrink your image (preferably 32x32)
3. ‘Project’ masks (rows of H) onto it and “measure” s using matrix multiplication
4. Multiply by H inverse to find i ($= H^{-1}s$)





- What are the unknowns in our system?
- Want to do an experiment to get information about these unknowns
- We can do a lot of interesting processing on vectors, but we need to convert the image into one first
 - In lecture and discussion, you have seen how to turn an image into a vector. How?



[0]	[1]
[2]	[3]
[4]	[5]



[0]	[1]
[2]	[3]
[4]	[5]

[0]
[1]


Images, Matrices, Vectors




[0]	[1]
[2]	[3]
[4]	[5]




[0]
[1]
[2]
[3]
[4]
[5]









Masked image




Image

Question Time


- To read all the pixels of a 4x4 image, how many pixel-by-pixel scans do we need to do?



Representing our Masks in Python





mask0 =
np.array([[1, 0, 0, 0, 0]
[0, 0, 0, 0, 0]
[0, 0, 0, 0, 0]
[0, 0, 0, 0, 0]
[0, 0, 0, 0, 0]])



Representing our Masks in Python

Imaging Mask 1




mask1 =

np.array([

0,	1,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0

)




Turning the Masks Into Vectors

5x5 mask to 25x1 vector


mask0 =

1	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



Row 0	1
Row 1	0
Row 2	0
Row 3	0
Row 4	0
	⋮
Row 24	0


T



Turning the Masks Into Vectors


mask1 =

0	1	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



Row 0	0
Row 1	1
Row 2	0
Row 3	0
Row 4	0
	⋮
Row 24	0


T



Generating the Masking Matrix from the Masks

mask0

1,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0



Generating the Masking Matrix from the Masks

mask0



1	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



1
0
0
0
0
...
0



Generating the Masking Matrix from the Masks



Generating the Masking Matrix from the Masks


mask1

0,	1,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0





0
1
0
0
0
...
0

1	0	0	0	0	0	0	0	...
---	---	---	---	---	---	---	---	-----



Generating the Masking Matrix from the Masks



1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
0	0	0	0	0	0	0	1	...
...								

Measuring a Pixel is Matrix-Vector Multiplication

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
...								

Masking Matrix H

i_1
i_2
i_3
i_n

Unknown,
vectorized
image, $\vec{i}$

=

s_1
s_2
s_3
s_n

Recorded
Sensor
readings, $\vec{s}$



$$\vec{s} = H\vec{l}$$

- We know H and we have the sensor readings, how do we get the image?
- How do we solve this?
- When can we solve this?
 - Conditions on H

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
0	0	0	0	0	0	0	1	...
...								

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
0	0	0	0	0	0	0	1	...
...								

How Scanning Works: iPython

H =

1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
...								



0
1
0
0
0
...
0



How Scanning Works: iPython

H =


1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
...								



0
1
0
0
0
...
0



0,	1,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0



How Scanning Works: iPython

H =



1	0	0	0	0	0	0	0	...
0	1	0	0	0	0	0	0	...
0	0	1	0	0	0	0	0	...
0	0	0	1	0	0	0	0	...
0	0	0	0	1	0	0	0	...
0	0	0	0	0	1	0	0	...
0	0	0	0	0	0	1	0	...
...								



0
1
0
0
0
...
0




0,	1,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0
0,	0,	0,	0,	0






What Makes a Mask Good?

- Linearly independent columns → Invertible
 - Can't get a solution without this
 - There is a unique solution
- What would be a bad mask?
- Food for thought: Are all invertible matrices equally as good?
 - Find out in Imaging 3 later this week




Cumulative Scanning

Identity
(H)



Alternating
(H_Alt)



Important Notes



1. Pick a simple image! Quality can be lost when resizing.
2. Use a short / simple imagePath name
 - a. you'll have to fill this in for some cells
 - b. default is the home directory for the lab
3. Before starting the simulations, open up the link (in the directions above the code cell) to the display view in a different tab & observe as the cell is running
4. Read simulation descriptions carefully!
 - a. you might have to manually set height & width because the defaults are 32x32
5. Each mask section includes ideal + noisy imaging
 - a. noisy imaging meant to simulate real projector behavior
 - b. don't worry about this for now -- more to come in Img 3

